

3 Wheel Electric Forklift Truck

Model	Unit	FE12S	FE15S	FE18S	FE20S
Power Type	-	Battery	Battery	Battery	Battery
Load Capacity	kg/lb.	1200/2640	1500/3300	1800/3960	2000/4400
Load Center	mm/in.	500/19.7	500/19.7	500/19.7	500/19.7
Max.Lift Height	mm/in.	3300/ 130.02	3300/ 130.02	3300/ 130.02	3300/ 130.02
Fork Size(L*W*T)	mm/in.	920x100 x35/ 36.25x3.94 x1.38	920x100 x35/ 36.25x3.94 x1.38	920x100 x35/ 36.25x3.94 x1.38	1070x122 x40/ 42.16x4.81 x1.58
Tilt Angle (Fwd/Bwd)	deg	5 / 6	5 / 6	5 / 6	5 / 6
Length to Fork Face	mm/in.	1830/72.10	1830/72.10	1940/76.45	2040/80.38
Overall Width	mm/in.	1070/42.16	1070/42.16	1070/42.16	1070/42.16
Mast Lowered Height	mm/in.	2135/84.12	2135/84.12	2135/84.12	2135/84.12
Overhead Guard Height	mm/in.	1990/78.41	1990/78.41	1990/78.41	1990/78.41
Min.Right Angle Aisle Width	mm/in.	3095/121.94	3095/121.94	3205/126.28	3305/130.22
Turning Radius (outside)	mm/in.	1400/55.16	1400/55.16	1510/59.49	1610/63.43
Wheelbase	mm/in.	1250/49.25	1250/49.25	1395/54.96	1460/57.52
Ground Clearance: Mast	mm/in.	100/3.90	100/3.90	100/3.90	100/3.90
Travel Speed	km/h	14.5/16.5	14.5/16.5	14.5/16.5	14.5/16.5
Weight (with battery)	kg/lb.	3100/6820	3280/7216	3485/7667	3750/8250
Driving Motor	kw	6.5x2	6.5x2	65.5x2	65.5x2
Lifting Motor	kw	12	12	12	12
Battery: voltage/ capacity	V/Ah	48/460	48/460	48/460	48/560
Battery Weight	kg/lb.	800/1760	800/1760	800/1760	1000/2200
Type of Drive Contorl	-	SME	SME	SME	SME
Transmission Case	-	PMP	PMP	PMP	PMP

FEED BACK FORM

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address:

