

## Diesel Forklift 5-10 Ton

Model	Unit	CPCD50	CPCD60	CPCD70	CPCD80	CPCD100
Power Type	-	Diesel				
Load Capacity	kg/lb.	5000/11000	6000/13200	7000/15400	8000/17600	10000/22000
Load Center	mm/in.	600/23.64	600/23.64	600/23.64	600/23.64	600/23.64
Max.Lift Height	mm/in.	3000/118.2	3000/118.2	3000/118.2	3000/118.2	3000/118.2
Free Lift Height	mm/in.	195/7.68	195/7.68	195/7.68	200/7.88	200/7.88
Fork Size(L*W*T)	mm/in.	1200x150x60/47.28x5.91x2.36		1200x150x65/47.28x5.91x2.56	1220x175x75/48.07x6.89x2.96	
Tilt Angle(Fwd/Bwd)	deg	6/12	6/12	6/12	6/12	6/12
Length to Fork Face	mm/in.	3472/136.80	3592/141.52	3592/141.52	3900/153.66	4120/162.33
Overall Width	mm/in.	1995/78.60	1995/78.60	1995/78.60	2165/85.30	2245/88.45
Overall Height Fork Raised	mm/in.	4419/174.11	4419/174.11	4419/174.11	4330/174.54	4330/174.54
Overhead Guard Height	mm/in.	2416/95.19	2416/95.19	2416/95.19	2560/100.86	2560/100.86
Min.Right Angle Aisle Width	mm/in.	3000/118.2	3090/121.75	3090/121.75	3540/139.48	3540/139.48
Turning Radius (outside)	mm/in.	3300/130.02	3450/135.93	3450/135.93	3700/145.78	3950/155.63
Travel Speed(with/with out)	km/h	28/26	28/26	28/26	28/26	28/26
Lifting Speed(with/with out)	mm/h	450/390	450/390	450/390	410/390	410/390
Max.Grade Ability	%	20	20	20	20	20
Ground Clearance:Mast	mm/in.	200/7.88			200/7.88	
Ground Clearance:Fram e	mm/in.	200/7.88			200/7.88	
Wheelbase	mm/in.	2250/88.65			2800/110.32	
Tread (Front/Rear)	mm/in.	1470(57.92)/1700(66.98)			1600(63.04)/1700(66.98)	
Self Weight	kg/lb.	8000/17600	8640/19000	9350/20570	11020/24244	12510/27522
Engine Model	-	ISUZU 6BG1				
Rated Output	kw/r.p.m	80.9 / 2500				
Rated Torque	NM/r.p.m	353 / 1600				
Displacement	cc	5785				

## FEED BACK FORM

E-mail:

Message:

Product Name:

---

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address: