
Electric Pallet Stacker

Model	Unit	XRS1535 (Two Stage Mast)	XWS1535 (Two Stage Mast)
Power Type	-	Battery	Battery
Load Capacity	Kg/lb.	1500/3300	1500/3300
Load Center	mm/in.	500/19.7	500/19.7
Standard Lifting Height	mm/in.	3500/137.9	3500/137.9
Fork Length	mm/in.	1130/44.52	1070/42.16
Fork Width	mm/in.	380/14.97	100(3.94)~850(33.49)
Overall Length	mm/in.	2428/95.66	1970/77.62(Without Platform)
Overall Width	mm/in.	850/33.49	1510/59.49
Overall Height;Fork Raised	mm/in.	4373/172.30 (Low Backrest)	4536/178.72 (High Backrest)
Leg Width	mm/in.	125/4.93	120/4.73
Leg Length	mm/in.	1147/45.19	851/33.53
Turning Radius (Outside)	mm/in.	1630/64.22	1450/57.13
Basic Right Angle Stacking Aisle Width (Add Load Length an clearance)	mm/in.	1600/63.04	1730/68.16
Total Weight (without battery)	Kg/lb.	1057/23254	1267/27874
Brake	-	Electric Wet Disk	Electric Wet Disk
Battery (Voltage/Capacity)	V/Ah	24/280	24/280
Control System	-	CURTIS	CURTIS

FEED BACK FORM

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address: